

## BSWM Series Battery Separators

### FEATURES

- Microprocessor controlled
- Provides priority for charging only the starter battery first
- Prevents excessive discharging of the starter battery
- Automatic detection for 12 or 24 Vdc system
- the existing circuit of the alternator (Euro 5/6)
- Bidirectional
- No voltage drop
- Gastight contacts
- Very low standby current
- 2 years warranty
- Works with old alternator and the latest Euro 5/6 norm vehicles

### APPLICATIONS

- Battery Separators are designed for use with 2 sets of batteries.
- It is recommended that these products be used with inverters when an auxillary battery is in use

- Ideal for:
  - Marine
  - Truck
  - RV / Automotive
  - Euro 5/6



## 160 AMPS

### TECHNICAL SPECIFICATIONS

Model	BSWM 160 Dual
Continuous Current	160 A
Peak Current	480 A (250msec)
Engine Vibrations Voltage*	(Euro 5/6)
Connect Voltage	>11.8 or >23.6 VDC
Disconnect Voltage	<11.6 or <23.2 VDC
Conventional mode Voltage*	(Old alternator)
Connect Voltage	13.2 or 26.4 VDC
Disconnect Voltage	12.8 or 25.6 VDC
Standby Current	1.8mA (12V) 2.0mA (24V)
Start Contact	Yes
Configure contact	Yes
Voltage Stability	±2%
Dimensions (LXWXD)	58X72X108 mm
Weight	0,47 Kgs

\* Combined mode is standard setting

Technical Specifications subject to change without notification