

ELOGIC INTELLIGENT DC-DC BATTERY CHARGER

FEATURES

- EURO 5/6 NORM
- Vehicle Charger
- Correct Charging
- Secondary Battery
- Programmable Software
- E11 Approval
- Operation Temp. -30°C - 70°C
- Current Limited
- 2 Year warranty

APPLICATIONS

- Standard and EURO5/6 Norm. Vehicles



30 AMPS

TECHNICAL SPECIFICATIONS

Model	EL 12-12/30 V2
Input Voltage Range	8 - 15 VDC
Output Voltage	10 - 15 VDC (programmable)
Output Current	30A
IP rating	IP-50
Output Ripple & Noise	<50mV RMS
Peak Efficiency	93%
Cooling	Convection Cooled
Operation Temperature	-30° to +70°C
Humidity, non condensing	Max 95%
Protection	Over current Over temperature Over voltage
Fuses Specs	
External Input Side Fuse (Inline with "Input+ Terminal)	32 V, 40 A
External Output Side Fuse (Inline with "Output+ Terminal)	32 V, 40 A
Approval	EMC / E11 (automotive)
Input / Output Connections	M6 terminals / Faston
Dimensions (LXWXH) incl. mousing flange	210X150X62 mm
Weight	1,0 Kgs

Technical Specifications subject to change without notification

To view a full selection of Samlex products visit our website at:
www.samlex.com or www.samlex-solar.com