

PS Series Pure Sinewave Inverter

FEATURES

- Pure sinewave AC output
- High surge power output
- High efficiency
- Protected against high/low battery voltage, low AC input voltage, over temperature, overload, short circuit etc.
- Variable fan speed for silent operation
- 2 year warranty



300 WATTS

TECHNICAL SPECIFICATIONS

Model	PS 350-24	
Inverter		
Output Power ¹⁾	P _{nom}	300 W
	P _{10minutes}	360 W
	P _{surge 3 sec}	800 W
Output voltage	230Vac ± 2%	
Output frequency	50Hz ± 0.05%	
Output waveform	True sinewave (THD <5% @ P _{nom})	
Admissible cos φ of load	0.2 - 1 (up to P _{nom})	
Input volgagge:	Nominal	24Vdc
	Range	21 ²⁾ - 31Vdc
Maximum efficiency	93%	
No load power consumption ³⁾	<3.5W	
[ASB]	[0.8W]	
ASB threshold	P _{out} 15W	
Operating temperature rang (ambient)	-20°C ... +50°C (humidity max 95% non condensing)	
Storage temperature range	-40°C ... +80°C (humidity max 95% non condensing)	
Cooling	Variable speed fan controlled by temperature and load	
Protected against	Short circuit, overload, high temperature, high/low battery voltage	
Indications	Power on, error and ASB mode	
DC input connections	2 x 1.5 mtr 4 mm ² cable	
AC output connections	Schuko outlet (standard)	
Enclosure body size (LxHxW)	184 x 98 x 130 mm	
Total weight	3,5 kg	
Protection class	IP20 (mounted in upright position)	
Standards	EN61000-6-3 (EN55022), EN61000-6-2 (EN61000-2/3/4, EN61000-4-3), LVD 73/23/EEC (EN60335-1)	

Note: the given specifications are subject to change without notice.

1) Measured with resistive load at 25°C ambient. Power ratings are subject to a tolerance of 10% and are decreasing as temperature rises with a rate of approx. 1.2%/°C starting from 25°C
2) Undervoltage limit is dynamic. This limit decreases with increasing load to compensate the voltage drop across cables and connections.
3) Measured at nominal input voltage and 25°C