

## IDC SERIES DC-DC CONVERTERS

### FEATURES

- Fully Isolated
- Short Circuit Protected
- Current Limited
- 2 Year warranty

### APPLICATIONS

- Earth moving equipment
- Heavy trucks
- Buses
- Marine
- Forklift
- Telecommunication



**100 Watts, fully isolated**

### TECHNICAL SPECIFICATIONS

Model	<b>IDC-100D-24</b>
Input Voltage Range	60-120 VDC
Output Voltage	24.5 VDC
Output Current	4 A
Input to Output Isolation	Yes >400 V RMS
Output Ripple & Noise	<50mV RMS
Peak Efficiency	85%
Operation Temperature	-20° to +30°C, De-rate linearly to zero at 70°C
Humidity, non condensing	Max 95%
Protection	Overload / short circuit on the output side Over Voltage on the output side Over Voltage / transients on the input side Reverse polarity on the input side Over heating
Fuses Specs	
External Input Side Fuse (Inline with "Input+Terminal)	125 V, 3 A
External Output Side Fuse (Inline with "Output+Terminal)	32 V, 5 A
Approval	CE and Automotive
Input / Output Connections	Quick Connect male 6.3 mm
Dimensions (LxWxH)	151x88x50 mm
Weight	0,5 Kgs

Technical Specifications subject to change without notification

To view a full selection of Samlex products visit our website at:  
[www.samlex.com](http://www.samlex.com) or [www.samlex-solar.com](http://www.samlex-solar.com)