

PSC Series Pure Sinewave Inverter/Charger

FEATURES

- Pure sinewave AC output
- High surge power output
- High efficiency
- 4-stage programmable battery charger
- Power factor corrected AC input
- Fast AC transfer switch
- AC Input Current Limit (adjustable)
- Protected against high/low battery voltage, low AC input voltage, over temperature, overload, short circuit etc.
- Variable fan speed for silent operation
- Remote on/off possibility
- Remote control capability by SamlexLink
- 2 year warranty



2600 WATTS

TECHNICAL SPECIFICATIONS

Model	PSC 3000-12-120
Inverter (factory setting/range adjustable with URC + SamlexLink)	
Nominal Battery Voltage	12 V
Input Voltage Range	10.5 - 16Vdc
Continuous Power @ 25°C	2600VA
Power 10 Min. @ 25°C	3200VA
Power 3 Sec. @ 25°C	5000VA
Maximum Load	Up to short-circuit
Maximum Asymmetric Load	Up to Pcont.
Load Detection (ASB threshold)	Variable (15-100W) (default : On @ Pout<20W / Off @ Pout>40W)
Cos Ø	0.1-1
Maximum Efficiency	92%
Consumption OFF/Stand-by/ON	0W / <3,5W / <20W
Output Voltage	Sine wave 230Vac (+/- 2%) / 185-270Vac
Output Frequency	50Hz/60Hz (-01) adjustable 45-65Hz +/- 0.05% (crystal controlled)
Harmonic Distortion	<2%
Overload And Short-Circuit Protection	Automatic disconnection with 3 time restart attempt
Overheat Protection	Warning before shut-off - with automatic restart
Battery charger 4 step programmable IUoUoP	
Charging Current Adjustable	0 - 120A (4A starter battery)
Input Current Balance Adjustment	2 - 16A
Maximum Input Voltage	260Vac
Input AC Voltage Range	Adjustable threshold from 150 to 265Vac
Input Frequency	45 - 65Hz
Power Factor Correction (PFC)	> 0.95
Battery control (factory setting/range adjustable URC + SamlexLink)	
Absorption End	By duration 4h or by current 10% Imax

TECHNICAL SPECIFICATIONS

Absorption Voltage	14.4 / 10.5 - 16V
Floating Voltage	13.6 / 10.5 - 16V
Equalization Voltage	10.5 - 16V
Absorption Timer	0 - 24h + infinite
Temp. Compensation (programmable)	-30mV / °C
General data	PSC 3000-12-120
Max. Current On Transfer Relay	30A
Transfer Time	0ms (inverter-mains) <5ms (mains-inverter)
Weight	19 Kgs
Dimension (LxWxH)	370x431x132 mm
Protection Index	IP21
Conformity	EMC directive/E2004/108/EC, LVD 2006/95/EC EN 60335-1, EN 60335-2-29 and RoHS 2002/95/EC
Operating Temperature Range	-20 to 50°C
Relative Humidity In Operation	95%
Ventilation	Forced from 50°C
Options	
URC	•
Samlexlink	•

Technical Specifications subject to change without notification